

Product datasheet:

- 60 minutes fire-resistant
- Applicable in hollow ceiling constructions.
- Suitable for rachel ceilings and metal stud ceilings.

Article number:  **AT8454-6**

EAN: 8712259552880

Dimensions / Form

Product Ø: 79 mm

Installation opening (wall/ceiling) Ø: 76 mm

Connections / Entries

Number of entries: 12

For conduit Ø: 19 mm

Assembly / Installation

Assembly type: hollow ceiling

Safety / Properties

Special application: Fire protection

Electrical Properties

Number of outputs: 6

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method: Hollow ceiling

Shape: Round

Construction type: Central conduit box

Model: Single

Provided with revolving ring: No

Couplable: No

Equipped with: Other

Diameter: 76 mm

Length:

Width:

Depth: 79 mm

Inner depth: 77 mm

Suitable for wall/board thickness: 25 mm

Suitable for number of device inserts:

Mounting switching equipment:

With screws: No



Product datasheet:

Number of non-adjustable device fixing lugs:

Number of adjustable device fixing lugs:

Housing feed-through by break-out opening: No

Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

Suitable for tube diameter: 16/19 mm

Suitable for cable diameter:

Pipe locking: No

Pipe locking optional: No

Inlet from the rear: No

Number of inlets: 12

Number of included spouts:

Material: Plastic

Halogen free: No

Surface protection: Untreated

Colour: Red

Degree of protection (IP): IP20

Degree of protection (NEMA):

Cover model: Mounting cover

Transparent cover: No

Cover attachment: Screwed

Sealable: No

Circuit integrity: E60

With screening:

Airtight:

Max. conductor cross section:

Number of poles of the clamp:

Clamp position fixed:

Luminaire hook mounting:

Nozzle: Tunnel branch pipe

Special application: Fire protection

With partition panel:

Compliant with BS 4662: