

Product datasheet:

- 60 minutes fire-resistant
- Applicable in hollow ceiling constructions.
- Suitable for rachel ceilings and metal stud ceilings.

Article number:  **AT8456-0**

EAN: 8712259552941

Dimensions / Form

Installation opening (wall/ceiling) Ø: 76 mm

Connections / Entries

Number of entries: 12

For conduit Ø: 19 mm

Assembly / Installation

Assembly type: hollow ceiling

Safety / Properties

Special application: Fire protection

Electrical Properties

Circuit: Series connection

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method: Hollow ceiling

Shape: Round

Construction type: Central conduit box

Model: Single

Provided with revolving ring: No

Couplable: No

Equipped with: Other

Diameter: 76 mm

Length:

Width:

Depth: 79 mm

Inner depth: 77 mm

Suitable for wall/board thickness: 25 mm

Suitable for number of device inserts:

Mounting switching equipment:

With screws: No

Number of non-adjustable device fixing lugs:



Product datasheet:

Number of adjustable device fixing lugs:

Housing feed-through by break-out opening:	No
--	----

Housing feed-through by seal membrane:	No
--	----

Housing feed-through by nozzle:	No
---------------------------------	----

Housing feed-through by step membrane:	No
--	----

Suitable for tube diameter:	16/19 mm
-----------------------------	----------

Suitable for cable diameter:	
------------------------------	--

Pipe locking:	No
---------------	----

Pipe locking optional:	No
------------------------	----

Inlet from the rear:	No
----------------------	----

Number of inlets:	12
-------------------	----

Number of included spouts:	
----------------------------	--

Material:	Plastic
-----------	---------

Halogen free:	No
---------------	----

Surface protection:	Untreated
---------------------	-----------

Colour:	Red
---------	-----

Degree of protection (IP):	IP20
----------------------------	------

Degree of protection (NEMA):	
------------------------------	--

Cover model:	Mounting cover
--------------	----------------

Transparent cover:	No
--------------------	----

Cover attachment:	Screwed
-------------------	---------

Sealable:	No
-----------	----

Circuit integrity:	E60
--------------------	-----

With screening:	
-----------------	--

Airtight:	
-----------	--

Max. conductor cross section:	
-------------------------------	--

Number of poles of the clamp:	
-------------------------------	--

Clamp position fixed:	
-----------------------	--

Luminaire hook mounting:	
--------------------------	--

Nozzle:	Tunnel branch pipe
---------	--------------------

Special application:	Fire protection
----------------------	-----------------

With partition panel:	
-----------------------	--

Compliant with BS 4662:	
-------------------------	--