

## Product datasheet:

|                        |                 |
|------------------------|-----------------|
| <b>Article number:</b> | <b>AT8523-2</b> |
| EAN:                   | 8712259605241   |

### Connections / Entries

|                    |    |
|--------------------|----|
| Number of entries: | 10 |
|--------------------|----|

### Electrical Properties

|                    |   |
|--------------------|---|
| Number of outputs: | 2 |
|--------------------|---|

### ETIM Product classification:

#### Box/housing for surface mounting on the wall/ceiling

|                                                                         |                        |
|-------------------------------------------------------------------------|------------------------|
| Model:                                                                  |                        |
| Equipped with:                                                          | Mounting plate         |
| Max. conductor cross section:                                           | 2,5 mm <sup>2</sup>    |
| Number of poles:                                                        |                        |
| Number of clamp positions per pole:                                     |                        |
| Shape:                                                                  | Rectangular            |
| Mounting method:                                                        | Wall-/ceiling mounting |
| Mounting in the soil:                                                   | No                     |
| Mounting under water:                                                   | No                     |
| Suitable for tube diameter:                                             |                        |
| Number of inlets:                                                       | 10                     |
| Inlet from the rear:                                                    | No                     |
| Length:                                                                 | 120 mm                 |
| Width:                                                                  | 95 mm                  |
| Depth:                                                                  | 60 mm                  |
| Diameter:                                                               |                        |
| Number of cable glands included:                                        |                        |
| Connectable:                                                            | No                     |
| Type of housing feed-through:                                           | Other                  |
| With strain relief:                                                     |                        |
| Material:                                                               | Plastic                |
| Halogen free:                                                           | No                     |
| Surface protection:                                                     |                        |
| Colour:                                                                 | Grey                   |
| RAL-number (similar):                                                   |                        |
| Degree of protection (IP):                                              | IP20                   |
| Degree of protection (NEMA):                                            |                        |
| Cover model:                                                            | Blind cover            |
| Outgoing connections with connectors for plug-in building installation: |                        |
| Transparent cover:                                                      | No                     |



## Product datasheet:

|                              |             |
|------------------------------|-------------|
| Castable:                    | No          |
| Cover attachment:            | Snapped on  |
| Casting compound included:   | No          |
| Sealable:                    | No          |
| Rated insulation voltage Ui: | 690 V       |
| Circuit integrity:           | None        |
| With screening:              | No          |
| Weatherproof:                | No          |
| Working temperature:         | -40 - 70 °C |
| Explosion-tested version:    | No          |
| Suitable for Ex-zone gas:    | None        |
| Suitable for Ex-zone dust:   | None        |