

## Product datasheet:

- Equipped with 1x power supply (male black), 1x power supply light point (male white), 2x light point connection (female white)
- Equipped with 1x power supply (male black), 1x power supply light point (male white), 2x light point connection (female white)

|                        |                 |
|------------------------|-----------------|
| <b>Article number:</b> | <b>AT8514-4</b> |
| EAN:                   | 8712259555478   |

### Connections / Entries

|                    |    |
|--------------------|----|
| Number of entries: | 10 |
|--------------------|----|

### Electrical Properties

|                    |   |
|--------------------|---|
| Number of outputs: | 4 |
|--------------------|---|

### ETIM Product classification:

#### Box/housing for surface mounting on the wall/ceiling

|                                     |                        |
|-------------------------------------|------------------------|
| Model:                              |                        |
| Equipped with:                      | Mounting plate         |
| Max. conductor cross section:       | 6 mm <sup>2</sup>      |
| Number of poles:                    |                        |
| Number of clamp positions per pole: |                        |
| Shape:                              | Rectangular            |
| Mounting method:                    | Wall-/ceiling mounting |
| Mounting in the soil:               | No                     |
| Mounting under water:               | No                     |
| Suitable for tube diameter:         | Other                  |
| Number of inlets:                   | 10                     |
| Inlet from the rear:                | No                     |
| Length:                             | 120 mm                 |
| Width:                              | 95 mm                  |
| Depth:                              | 80 mm                  |
| Diameter:                           |                        |
| Number of cable glands included:    |                        |
| Connectable:                        | No                     |
| Type of housing feed-through:       | Other                  |
| With strain relief:                 |                        |
| Material:                           | Plastic                |
| Halogen free:                       | No                     |
| Surface protection:                 | Untreated              |
| Colour:                             | Grey                   |
| RAL-number (similar):               |                        |
| Degree of protection (IP):          | IP20                   |
| Degree of protection (NEMA):        |                        |



## Product datasheet:

|                                                                         |             |
|-------------------------------------------------------------------------|-------------|
| Cover model:                                                            | Blind cover |
| Outgoing connections with connectors for plug-in building installation: |             |
| Transparent cover:                                                      | No          |
| Castable:                                                               | No          |
| Cover attachment:                                                       | Snapped on  |
| Casting compound included:                                              | No          |
| Sealable:                                                               | No          |
| Rated insulation voltage Ui:                                            | 690 V       |
| Circuit integrity:                                                      | None        |
| With screening:                                                         | No          |
| Weatherproof:                                                           | No          |
| Working temperature:                                                    | -40 - 70 °C |
| Explosion-tested version:                                               | No          |
| Suitable for Ex-zone gas:                                               | None        |
| Suitable for Ex-zone dust:                                              | None        |