Product datasheet:

· Distribution and power supply of WCDs, device or central box/cable box.

Article number:	**AT8530-2**
EAN:	8712259554259

Connections / Entries

Number of entries:	10

Electrical Properties

Number of outputs:	2

ETIM Product classification:
Box/housing for surface mounting on the wall/ceiling

Model:	
Equipped with:	Mounting plate
Max. conductor cross section:	6 mm²
Number of poles:	
Number of clamp positions per pole:	
Shape:	Rectangular
Mounting method:	Wall-/ceiling mounting
Mounting in the soil:	No
Mounting under water:	No
Suitable for tube diameter:	Other
Number of inlets:	10
Inlet from the rear:	No
Length:	120 mm
Width:	95 mm
Depth:	60 mm
Diameter:	
Number of cable glands included:	
Connectable:	No
Type of housing feed-through:	Other
With strain relief:	
Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Grey
RAL-number (similar):	
Degree of protection (IP):	IP20
Degree of protection (NEMA):	
Cover model:	Blind cover

Product datasheet:

Outgoing connections with connectors for plug-in building installation:	
Transparent cover:	No
Castable:	No
Cover attachment:	Snapped on
Casting compound included:	No
Sealable:	No
Rated insulation voltage Ui:	690 V
Circuit integrity:	None
With screening:	No
Weatherproof:	No
Working temperature:	-40 - 70 °C
Explosion-tested version:	No
Suitable for Ex-zone gas:	None
Suitable for Ex-zone dust:	None