# Product datasheet:

· Equipped with 1x power supply (male black), 2x switch (female brown), 1x light point connection (female white)

| **Article number:** | **AT8508-4** |
|---|---|
| EAN: | 8712259554129 |

**Connections / Entries**

| | |
|---|---|
| Number of entries: | 10 |

**Electrical Properties**

| | |
|---|---|
| Number of outputs: | 4 |
| Circuit: | Changeover switch |

## ETIM Product classification:
## Box/housing for surface mounting on the wall/ceiling

| | |
|---|---|
| Model: | |
| Equipped with: | Mounting plate |
| Max. conductor cross section: | 6 mm² |
| Number of poles: | |
| Number of clamp positions per pole: | |
| Shape: | Rectangular |
| Mounting method: | Wall-/ceiling mounting |
| Mounting in the soil: | No |
| Mounting under water: | No |
| Suitable for tube diameter: | Other |
| Number of inlets: | 10 |
| Inlet from the rear: | No |
| Length: | 120 mm |
| Width: | 95 mm |
| Depth: | 80 mm |
| Diameter: | |
| Number of cable glands included: | |
| Connectable: | No |
| Type of housing feed-through: | Other |
| With strain relief: | |
| Material: | Plastic |
| Halogen free: | No |
| Surface protection: | Untreated |
| Colour: | Grey |
| RAL-number (similar): | |
| Degree of protection (IP): | IP20 |

# Product datasheet:

| | |
|---|---|
| Degree of protection (NEMA): | |
| Cover model: | Blind cover |
| Outgoing connections with connectors for plug-in building installation: | |
| Transparent cover: | No |
| Castable: | No |
| Cover attachment: | Snapped on |
| Casting compound included: | No |
| Sealable: | No |
| Rated insulation voltage Ui: | 690 V |
| Circuit integrity: | None |
| With screening: | No |
| Weatherproof: | No |
| Working temperature: | -40 - 70 °C |
| Explosion-tested version: | No |
| Suitable for Ex-zone gas: | None |
| Suitable for Ex-zone dust: | None |