

Product datasheet:

Sealing systems in fire-protection walls

- Simple, dry, clean and efficient way of sealing hole Ø 25 mm fire resistant.
- Classification EI90/EW90.
- Applicable in a fire resistant wall of 30, 60 and 90 minutes.
- Applicable in combination with wire/cable in pipe, (data) cable and connection cable up to Ø 22 mm.
- Applicable during the installation process and afterwards.

Article number: **AT1521**

EAN: 8712259370798

Packaging quantity: 50

Dimensions / Form

Installation opening (wall/ceiling) Ø: 20 mm

Safety / Properties

Halogen-free: Yes

ETIM Product classification: Fire partitioning

Model: Finished fire partition

Shape: Round

Outer height:

Outer width:

Outer diameter:

Inner height:

Inner width:

Inner diameter:

Depth:

Plate thickness/product length:

Min. wall thickness:

Min. ceiling thickness:

Suitable for max. cable diameter:

Accessories required: No

Suitable for drywall:

Suitable for solid wall:

Suitable for solid floor:

Suitable for flush floor installation:

Suitable for flush ceiling installation:

Suitable for empty plastic pipes:

Min. clearance required within the fire penetration seal:

Fire partitioning assignable to 100%:



Assembly instructions



Certificates

Product datasheet:

Max. pressure:

Weatherproof:

Min. fire resistance class according to EN
13501-2:

Max. fire resistance class according to EN
13501-2:

Content bucket/bag:

Volume can/cartouche:

Fire resistance class according to DIN
4102-9:

Fire-retardant systems for safe closure of passages and entrances in fire-protection walls.
The certified retardants are quick and easy to install and can even be superimposed on
cables and pipes retrospectively.