

Product datasheet:

Sealing systems in fire-protection walls

- Identification sticker for logbook and project administration fire-resistant transits.
- To be installed next to the fire-resistant penetrations.

Article number:	⇒ AT1525
EAN:	8712259509556
Packaging quantity:	100

Dimensions / Form

Product length:	135 mm
Product depth:	89 mm

Safety / Properties

Halogen-free:	Yes
---------------	-----



ETIM Product classification: Fire partitioning

Model:	Other
Shape:	Quadrangular
Outer height:	
Outer width:	
Outer diameter:	
Inner height:	
Inner width:	
Inner diameter:	
Depth:	
Plate thickness/product length:	1 mm
Min. wall thickness:	
Min. ceiling thickness:	
Suitable for max. cable diameter:	
Accessories required:	No
Suitable for drywall:	
Suitable for solid wall:	
Suitable for solid floor:	
Suitable for flush floor installation:	
Suitable for flush ceiling installation:	
Suitable for empty plastic pipes:	
Min. clearance required within the fire penetration seal:	
Fire partitioning assignable to 100%:	
Max. pressure:	

Product datasheet:

Weatherproof:

Min. fire resistance class according to EN
13501-2:

Max. fire resistance class according to EN
13501-2:

Content bucket/bag:

Volume can/cartouche:

Fire resistance class according to DIN
4102-9:

Fire-retardant systems for safe closure of passages and entrances in fire-protection walls.
The certified retardants are quick and easy to install and can even be superimposed on
cables and pipes retrospectively.