

Product datasheet:

Box sealing system DS 90 / 120 mm

Sealing systems in fire-protection walls

- for F30-F90 or EI30-EI90 fire-protection walls
- attachment using tried-and-tested FX⁴ metal plate screws
- with integrated sealing inserts
- ensures smoke-tight room separation (seals against cold smoke)
- unlimited building material shelf life



Article number:	GD 9459-04NL
EAN:	4013456551718
Packaging quantity:	4

Dimensions / Form

Drill/cut hole Ø:	120 mm
-------------------	--------

Assembly / Installation

Wall thickness min.:	100 mm
Wall thickness max.:	100 mm

Safety / Properties

Sound insulation walls up to:	72
Sound insulation:	Yes

Approvals / Certifications

fire resistance class:	EI 90
DIBT approval:	Z-19.53-2188

ETIM Product classification: Fire partitioning

Model:	Other
Shape:	Round
Outer height:	
Outer width:	
Outer diameter:	
Inner height:	
Inner width:	
Inner diameter:	
Depth:	
Plate thickness/product length:	100 mm
Min. wall thickness:	
Min. ceiling thickness:	
Suitable for max. cable diameter:	



Assembly instructions



Certificates



Technical information

Product datasheet:

Accessories required: No

Suitable for drywall:

Suitable for solid wall:

Suitable for solid floor:

Suitable for flush floor installation:

Suitable for flush ceiling installation:

Suitable for empty plastic pipes:

Min. clearance required within the fire penetration seal:

Fire partitioning assignable to 100%:

Max. pressure:

Weatherproof:

Min. fire resistance class according to EN 13501-2:

Max. fire resistance class according to EN 13501-2:

Content bucket/bag:

Volume can/cartouche:

Fire resistance class according to DIN 4102-9:

Fire-retardant systems for safe closure of passages and entrances in fire-protection walls. The certified retardants are quick and easy to install and can even be superimposed on cables and pipes retrospectively.