

Product datasheet:

AK2-S/MK Cable box cable duct

Cable-mate® cableboxes for dry indoor use

- Packed per junction box 3 KBS 16 mm slide inlets and 1 shutter slide.
- Design with a compact MK assembly plate for quick click-assembly on the side of the cable duct.
- Suitable for all common cable duct brands.
- Can also be fitted underneath some cable ducts.
- Matching AK2 front part can be ordered separately.
- Each article is packaged with 3x KBS 16 mm inlets and 1 locking slider
- Matching AK2 front part can be ordered separately
- Suitable for cable support systems from well-known manufacturers

Distribution box AK2 according to DIN EN 60670, for plug-in electrical installation, base housing

with electric cable and conduit entries for cables $\varnothing$ 8-14 mm, for conduits max. $\varnothing$ 16 mm, dimensions L x W x H: 120 x 95 x 40 mm

Protection class: IP40

Rated voltage: 690 V

Mounting: including mounting clip for fixing to cable trays

Colour: grey

Halogen-free



Article number: **⇒ AT2216**

E-No: 127018199

EAN: 8712259298849

Packaging quantity: 15

Dimensions / Form

Product length: 120 mm

Product width: 95 mm

Product depth: 40 mm

Connections / Entries

Number of entries: 10

For conduit $\varnothing$: 16 mm

Assembly / Installation

Fastening type (other): Hole matrix

Safety / Properties

Halogen-free: Yes

Material / Colour

Colour designation: Light grey

Approvals / Certifications

VDE: Yes

Product datasheet:

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	70 °C

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.