

Product datasheet:

Cable-mate® cableboxes for dry indoor use

- Packed per junction box 3 KBS 16 mm slide inlets and 1 shutter slide.
- Pre-assembled on plastic mounting plate MD for quick click-connection.
- Matching AK2 front part can be ordered separately.
- Universally applicable for all brands of wire tray.



Article number:	AT2229.01
EAN:	8712259603490
Packaging quantity:	100

Connections / Entries

Number of entries:	10
For conduit Ø:	16 mm

Safety / Properties

Halogen-free:	Yes
---------------	-----



Material / Colour

Colour:	black
---------	-------

ETIM Product classification:

Box/housing for surface mounting on the wall/ceiling

Model:	
Equipped with:	Mounting plate
Max. conductor cross section:	6 mm ²
Number of poles:	
Number of clamp positions per pole:	
Shape:	Rectangular
Mounting method:	On cable tray
Mounting in the soil:	No
Mounting under water:	No
Suitable for tube diameter:	16 mm
Number of inlets:	10
Inlet from the rear:	No
Length:	120 mm
Width:	95 mm
Depth:	40 mm
Diameter:	
Number of cable glands included:	
Connectable:	No
Type of housing feed-through:	Preembossing
With strain relief:	

Product datasheet:

Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Black
RAL-number (similar):	
Degree of protection (IP):	IP40
Degree of protection (NEMA):	
Cover model:	None
Outgoing connections with connectors for plug-in building installation:	
Transparent cover:	No
Castable:	No
Cover attachment:	Snapped on
Casting compound included:	No
Sealable:	No
Rated insulation voltage Ui:	690 V
Circuit integrity:	None
With screening:	No
Weatherproof:	No
Working temperature:	-40 - 70 °C
Explosion-tested version:	No
Suitable for Ex-zone gas:	None
Suitable for Ex-zone dust:	None

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.