

Product datasheet:

AK2-S/GZ IP40

Cable-mate® cableboxes for dry indoor use

- Packed per junction box 3 KBS 16 mm slide inlets and 1 shutter slide.
- Matching AK2 front part can be ordered separately.
- Suitable for cable trays from Legrand (Van Geel), Stago, Niedax, Vergokan, PUK and OBO.
- Each article is packaged with 3x KBS 16 mm inlets and 1 locking slider
- Suitable for cable support systems from well-known manufacturers

distribution enclosure AK2 in accordance with DIN EN 60670, for plug-in electrical installation, base enclosure with electric cable and conduit entries for electric cables with a diameter of 8-14 mm, for conduits with a maximum diameter of 16 mm, dimensions L x W x H: 120 x 95 x 40 mm

Protection class: IP40

Rated voltage: 690 V

Mounting: including angled mounting plate, for fixing to cable trays,



Article number: **AT2251**

EAN: 8712259161518

Packaging quantity: 10

Price group: 250

Dimensions / Form

Product length: 120 mm

Product width: 95 mm

Product depth: 40 mm

Connections / Entries

Number of entries: 10

For conduit Ø: 16 mm

Assembly / Installation

Fastening type (other): Angled mounting plate

Safety / Properties

Halogen-free: Yes

Material / Colour

Colour designation: Light grey

Approvals / Certifications

VDE: Yes

Storage / Installation / Operation

Minimum operating temperature: -40 °C

Maximum operating temperature: 70 °C

Product datasheet:

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.