

Product datasheet:

AK2-SU enclosure base IP40

Cable-mate® cableboxes for dry indoor use

- For wall mounting (not suitable for attachment to wiring-duct mounting plate).
- Each cable box includes 3 slide-in KBS 16 mm and 1 slide-in blind cover.
- Matching AK2 front part can be ordered separately.
- Each article is packaged with 3x KBS 16 mm inlets and 1 locking slider
- Suitable for cable support systems from well-known manufacturers

AK2 distribution box in accordance with DIN EN 60670, for plug-in electrical installation, base box
with electric cable and conduit entries for electric cables with a diameter of 8-14 mm, for conduits with a maximum diameter of 16 mm, dimensions L x W x H: 120 x 95 x 40 mm
Protection class: IP40
Rated voltage: 690 V
Mounting: Surface mounting
Colour: Grey
Halogen-free



Article number:	➔ AT2258
E-No:	157892109
EAN:	8712259264745
Packaging quantity:	15

Dimensions / Form

Product length:	120 mm
Product width:	95 mm
Product depth:	40 mm

Connections / Entries

Number of entries:	10
For conduit Ø:	16 mm

Assembly / Installation

Fastening type (other):	Screw holes
-------------------------	-------------

Safety / Properties

Halogen-free:	Yes
---------------	-----

Material / Colour

Colour designation:	Light grey
---------------------	------------

Approvals / Certifications

VDE:	Yes
------	-----

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	70 °C

Product datasheet:

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.