

Product datasheet:

AK2-IP40

Cable-mate® cableboxes for dry indoor use

- Metric input M20.
- Especially for mounting on steel mounting plates of cable trays.
- 3 cable/tube entries KBI 16 mm and 1 quick fastening screw are packed per cable box.



Article number: **↗ AT2291**

EAN: 8712259088600

Packaging quantity: 100

Connections / Entries

Number of entries: 8

For conduit Ø: 16 mm

Safety / Properties

Halogen-free: Yes

Material / Colour

Colour designation: Light grey



ETIM Product classification:

Box/housing for surface mounting on the wall/ceiling

Model:

Equipped with: Other

Max. conductor cross section: 6 mm²

Number of poles:

Number of clamp positions per pole:

Shape: Rectangular

Mounting method: Universal

Mounting in the soil: No

Mounting under water: No

Suitable for tube diameter: 16 mm

Number of inlets: 8

Inlet from the rear: No

Length: 120 mm

Width: 95 mm

Depth: 45 mm

Diameter:

Number of cable glands included:

Connectable: No

Type of housing feed-through: Thread and prestamping

Product datasheet:

With strain relief:

Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Grey
RAL-number (similar):	
Degree of protection (IP):	IP40
Degree of protection (NEMA):	
Cover model:	Blind cover
Outgoing connections with connectors for plug-in building installation:	
Transparent cover:	No
Castable:	No
Cover attachment:	Snapped on
Casting compound included:	No
Sealable:	No
Rated insulation voltage Ui:	690 V
Circuit integrity:	None
With screening:	No
Weatherproof:	No
Working temperature:	-40 - 70 °C
Explosion-tested version:	No
Suitable for Ex-zone gas:	None
Suitable for Ex-zone dust:	None

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.