

## Product datasheet:

# Flat box, 2x3p black + connection wires Wieland

## Cable-mate® cableboxes for dry indoor use

- Suitable for mounting in suspended ceilings and underfloor areas.
- Equipped with VD wire 2.5 mm<sup>2</sup>.
- All connectors are equipped with locking.
- Connection via prefabricated 2.5 mm<sup>2</sup> core cable
- Suitable for mounting in suspended ceilings and underfloor areas
- Suitable M20 cable gland for a 3x1.5 mm<sup>2</sup> or 3x2.5 mm<sup>2</sup> feed line: AGRO Progress 1571.20.110
- Suitable cable M20 cable gland for two feed lines 3x1.5 mm<sup>2</sup>: AGRO Progress 1571.20.2.075

Compact PD distribution box in accordance with DIN EN 60670, for plug-in electrical installation, internal wiring: 2.5 mm<sup>2</sup>

Dimensions L x W x H: 120 x 120 x 40 mm

Protection class: IP20

Rated voltage: 400 V

Input: 1 x H07V-U cable, 3-pole

Output: 2 x Wieland GST18 black plug connectors, 3-pole

Installation: for installation in suspended ceilings and underfloor areas

Colour: grey

Halogen-free



**Article number:** **➔ AT2530**

EAN: 8712259247205

Packaging quantity: 10

Price group: 250

### Dimensions / Form

Product length: 120 mm

Product width: 120 mm

Product depth: 40 mm

### Connections / Entries

Number of entries: 2

### Safety / Properties

Halogen-free: Yes

### Electrical Properties

Pre-wiring: 2.5

### Approvals / Certifications

Protection class: IP20

### Storage / Installation / Operation

Minimum operating temperature: -40 °C

Maximum operating temperature: 70 °C

## Product datasheet:

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.