

Product datasheet:

Flat box, 2x3p black + connection wires Wieland

Cable-mate® cableboxes for dry indoor use

- Including mounting plate and cover.
- Dimensions: 120 x 120 x 40 mm.
- Box can be adjusted in any direction.
- Quick installation on various central boxes and flush-mounted boxes.
- For possibilities of hole pattern, see the assembly instructions.
- Suitable for installation in bed headboards, hollow walls and furniture; glow-wire tested at 850°C.
- Suitable for mounting in suspended ceilings and underfloor areas.
- Equipped with VD wire 2.5 mm².
- All connectors are equipped with locking.
- Connection via prefabricated 2.5 mm² core cable
- Suitable for mounting in suspended ceilings and underfloor areas
- Suitable M20 cable gland for a 3x1.5 mm² or 3x2.5 mm² feed line: AGRO Progress 1571.20.110
- Suitable cable M20 cable gland for two feed lines 3x1.5 mm²: AGRO Progress 1571.20.2.075



Compact PD distribution box in accordance with DIN EN 60670, for plug-in electrical installation, internal wiring: 2.5 mm²

Dimensions L x W x H: 120 x 120 x 40 mm

Protection class: IP20

Rated voltage: 400 V

Input: 1 x H07V-U cable, 3-pole

Output: 2 x Wieland GST18 black plug connectors, 3-pole

Installation: for installation in suspended ceilings and underfloor areas

Colour: grey

Halogen-free

Article number: **AG AT2530**

E-No: 157891119

EAN: 8712259247205

Packaging quantity: 10

Dimensions / Form

Product length: 120 mm

Product width: 120 mm

Product depth: 40 mm

Connections / Entries

Number of entries: 2

Safety / Properties

Halogen-free: Yes

Electrical Properties

Pre-wiring: 2.5

Product datasheet:

Approvals / Certifications

Protection class:	IP20
-------------------	------

Storage / Installation / Operation

Minimum operating temperature:	-40 °C
Maximum operating temperature:	70 °C

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.