

Product datasheet:

Flat Box, 2x3p black + 1x3p black male WAGO

Cable-mate® cableboxes for dry indoor use

- Suitable for mounting in suspended ceilings and underfloor areas.
- Equipped with VD wire 2.5 mm².
- All connectors are equipped with locking.

Compact PD distribution box in accordance with DIN EN 60670, for pluggable electrical installation, 100% pluggable

Internal wiring: 2.5 mm²

Dimensions L x W x H: 120 x 120 x 40 mm

Protection class: IP20

Rated voltage: 400 V

Input: 1 x WAGO WINSTA MIDI black plug connector, 3-pin

Output: 2 x WAGO WINSTA MIDI black plug connectors, 3-pin

Installation: for installation in suspended ceilings and underfloor areas

Colour: Grey

Halogen-free



Article number: **GD AT3217**

EAN: 8712259328058

Packaging quantity: 10

Price group: 250

Dimensions / Form

Product length: 120 mm

Product width: 120 mm

Product depth: 40 mm

Connections / Entries

Number of entries: 3

Safety / Properties

Halogen-free: Yes

Electrical Properties

Pre-wiring: 2.5

Approvals / Certifications

Protection class: IP20

Storage / Installation / Operation

Minimum operating temperature: -40 °C

Maximum operating temperature: 70 °C

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common

Product datasheet:

raceways.