

Product datasheet:

Flat Box, 2x3p black + 1x3p black male WAGO

Cable-mate® cableboxes for dry indoor use

- Including mounting plate and cover.
- Dimensions: 120 x 120 x 40 mm.
- Box can be adjusted in any direction.
- Quick installation on various central boxes and flush-mounted boxes.
- For possibilities of hole pattern, see the assembly instructions.
- Suitable for mounting in suspended ceilings and underfloor areas.
- Equipped with VD wire 2.5 mm².
- All connectors are equipped with locking.



Compact PD distribution box in accordance with DIN EN 60670, for pluggable electrical installation, 100% pluggable

Internal wiring: 2.5 mm²

Dimensions L x W x H: 120 x 120 x 40 mm

Protection class: IP20

Rated voltage: 400 V

Input: 1 x WAGO WINSTA MIDI black plug connector, 3-pin

Output: 2 x WAGO WINSTA MIDI black plug connectors, 3-pin

Installation: for installation in suspended ceilings and underfloor areas

Colour: Grey

Halogen-free



Article number: **➔ AT3217**

EAN: 8712259328058

Packaging quantity: 10

Dimensions / Form

Product length: 120 mm

Product width: 120 mm

Product depth: 40 mm

Connections / Entries

Number of entries: 3

Safety / Properties

Halogen-free: Yes

Electrical Properties

Pre-wiring: 2.5

Approvals / Certifications

Protection class: IP20

Storage / Installation / Operation

Minimum operating temperature: -40 °C

Maximum operating temperature: 70 °C

Product datasheet:

ETIM Product classification:

Box/housing for surface mounting on the wall/ceiling

Model:	
Equipped with:	Other
Max. conductor cross section:	4 mm ²
Number of poles:	
Number of clamp positions per pole:	
Shape:	Square
Mounting method:	Universal
Mounting in the soil:	No
Mounting under water:	No
Suitable for tube diameter:	
Number of inlets:	3
Inlet from the rear:	No
Length:	120 mm
Width:	120 mm
Depth:	40 mm
Diameter:	
Number of cable glands included:	
Connectable:	No
Type of housing feed-through:	Preembossing
With strain relief:	
Material:	Plastic
Halogen free:	No
Surface protection:	Untreated
Colour:	Grey
RAL-number (similar):	
Degree of protection (IP):	IP20
Degree of protection (NEMA):	
Cover model:	Blind cover
Outgoing connections with connectors for plug-in building installation:	
Transparent cover:	No
Castable:	No
Cover attachment:	Snapped on
Casting compound included:	No
Sealable:	No
Rated insulation voltage Ui:	400 V
Circuit integrity:	None
With screening:	No

Product datasheet:

Weatherproof:	No
Working temperature:	-40 - 70 °C
Explosion-tested version:	No
Suitable for Ex-zone gas:	None
Suitable for Ex-zone dust:	None

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.