

Product datasheet:

AK2-W8 Cover, 3x3p Wieland

Cable-mate® cableboxes for dry indoor use

- Equipped with VD wire 2.5 mm².
- All connectors are equipped with locking.
- Prefabricated with connection wires 2.5 mm²
- Suitable for WAGO WINSTA® MIDI or Wieland gesis® CLASSIC GST18®

Front part for AK2 distribution enclosure in accordance with DIN EN 60670, for plug-in electrical installation, internal wiring: 2.5 mm²

Dimensions L x W x H: 125 x 100 x 42 mm

Protection class: IP20

Rated voltage: 400 V

Input: 1 x H07V-U cable, 3-pole L1 / N / PE

Output: 3 x Wieland GST18 black plug connectors, 3-pole

Mounting: for mounting on AK2 base housing

Colour: grey

Halogen-free



Article number: **AT6031**

EAN: 8712259182674

Packaging quantity: 10

Dimensions / Form

Product length: 125 mm

Product width: 100 mm

Product depth: 42 mm

Material / Colour

Colour designation: Light grey

Electrical Properties

Pre-wiring: 2.5

Plug connector type: Wieland GST18

Approvals / Certifications

Protection class: IP20

ETIM Product classification:

Cover for box/housing for surface mounting on the wall/ ceiling

Diameter:

Length: 125 mm

Width: 100 mm

Depth: 42 mm

Shape: Rectangular

Type of fastening: Click

Product datasheet:

Model:	Suitable for snap-in connector (manufacturer specific)
Colour:	Grey
Transparent:	No
RAL-number:	
With connection cable:	No
Number of socket outlets:	
Number of 3-pole connectors:	3
Number of 4-pole connectors:	0
Number of 5-pole connectors:	0
Outgoing connections with connectors for plug-in building installation:	
Degree of protection (IP):	IP20
Degree of protection (NEMA):	

Cable-mate® is the innovative, award-winning cable box system that excels in terms of time savings and ease of installation. There is a wide selection of versatile cover material that can be attached to the cable box easily, without screws. The completely renovated raceway click attachment system makes rapid installation possible on all common raceways.