

Product datasheet:

CA70R Junction box 16/19 mm with tape Ø 16/19 mm

Central junction boxes concrete ceiling

- Equipped with 9 combi-heads 16/19 mm.
- Applicable in solid floors and hollow core slab floors.
- Clip-resistant in borehole Ø 80 mm.
- Matching covers: (art. no. AT5010 and art. no. AT5011).



Article number: **↗ AT1019**

EAN: 8712259314419

Packaging quantity: 100

Dimensions / Form

Product Ø: 115 mm

Installation opening (wall/ceiling) Ø: 80 mm



Connections / Entries

Number of entries: 9

For conduit Ø: 19 mm

Safety / Properties

Halogen-free: Yes

ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method: Concrete building

Shape: Round

Construction type: Central conduit box

Model: Single

Provided with revolving ring: No

Couplable: No

Equipped with: None

Diameter: 78 mm

Length:

Width:

Depth:

Inner depth: 70 mm

Suitable for wall/board thickness:

Suitable for number of device inserts: 0

Mounting switching equipment:

With screws: No

Product datasheet:

Number of non-adjustable device fixing lugs:

Number of adjustable device fixing lugs:

Housing feed-through by break-out opening: No

Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

Suitable for tube diameter: 16/19 mm

Suitable for cable diameter:

Pipe locking: No

Pipe locking optional: No

Inlet from the rear: No

Number of inlets: 9

Number of included spouts: 0

Material: Plastic

Halogen free: No

Surface protection: Untreated

Colour: Grey

Degree of protection (IP): IP20

Degree of protection (NEMA):

Cover model: None

Transparent cover: No

Cover attachment: Screwed

Sealable: No

Circuit integrity: None

With screening: No

Airtight: No

Max. conductor cross section: 6 mm²

Number of poles of the clamp: 0

Clamp position fixed: No

Luminaire hook mounting: No

Nozzle: Tunnel branch pipe

Special application: None

With partition panel:

Compliant with BS 4662:

The concrete ceiling junction boxes are specially developed for the installation of conventional systems in concrete ceilings. These junction boxes are equipped with combi-inlets combined for 16 mm and 19 mm conduits. The ceiling junction boxes Concrete are used in solid floors and concrete hollow-core floors, or precast slab floors.