

Product datasheet:

Plaster compensation ring, round junction boxes

Central junction boxes hollow ceiling

- Stackable underneath.
- Universally applicable on any round central box.
- Application: thick(er) ceiling tiles (e.g. 2 x 12.5 mm plasterboard).
- Raising edge not provided with inserts and M4 screws not provided.



Article number: **➔ AT1515**

EAN: 8712259530703

Packaging quantity: 50

Dimensions / Form

Product depth: 15 mm



Safety / Properties

Halogen-free: Yes

ETIM Product classification: Plaster compensation ring

Levelling height: 15 mm

Length:

Width:

Diameter: 76 mm

Shape: Round

With cover: No

Application: Central conduit box

Mounting method: Flush-mounted

Extension ring: No

The junction boxes for hollow ceilings can be used in any situation in the hollow ceiling structure. In rachel wood ceilings (eg. 18 mm and 22 mm) and metal Metal Stud ceilings (eg. 27 mm). Suitable for ceiling panel thicknesses of eg 9.5 mm, 12.5 mm and 25 mm. Applicable in standard and fire-resistant ceiling structures. The round shape of the junction boxes is easily applied in the ceiling plate when drilling the correct hole diameter (Ø 76 mm). The ceiling junction boxes are equipped with 12 combi-inlets. Suitable for 16 mm or 19 mm conduits and cable (via cable strain relief, Art. No. AT1062). The junction boxes can be performed pluggable with WINSTA RD connectors.