

Product datasheet:

Ceiling junction box cover, square with terminal block

Central junction boxes hollow ceiling

- Quick assembly thanks to plug-in contacts with spring clamp.
- The plug-in clamp is provided with a protective cover.
- Flat design, so that the welding space in the central box is used optimally.
- Suspension hook and 2 screws M4x14 fixed in the lid.
- M4 bolts fitted with a combi head; suitable for automatic screwdriver.
- Universally applicable to any square central box.



Article number: **⇒ AT4015**

EAN: 8712259004129

Packaging quantity: 100

Safety / Properties

Halogen-free: Yes



ETIM Product classification:

Cover for box/housing for built-in mounting in the wall/ceiling

Diameter:

Suitable for box-/housing diameter:

Length:

Suitable for box-/housing length:

Width:

Suitable for box-/housing width:

Depth:

Shape: Square

Type of fastening:

Model: Cover with hook

With cable outlet: No

Material: Plastic

Halogen free:

Colour: Other

RAL-number (similar):

With screws:

Sealable:

The junction boxes for hollow ceilings can be used in any situation in the hollow ceiling structure. In rachel wood ceilings (eg. 18 mm and 22 mm) and metal Metal Stud ceilings (eg. 27 mm). Suitable for ceiling panel thicknesses of eg 9.5 mm, 12.5 mm and 25 mm. Applicable in standard and fire-resistant ceiling structures. The round shape of the junction boxes is easily applied in the ceiling plate when drilling the correct hole diameter (Ø 76 mm). The ceiling junction boxes are equipped with 12 combi-inlets. Suitable for 16 mm or 19 mm conduits and cable (via cable strain relief, Art. No.

Product datasheet:

AT1062). The junction boxes can be performed pluggable with WINSTA RD connectors.