

# Product datasheet:

## Main switch boxes

Article number: **AT91019**

EAN: 8712259533896

### Dimensions / Form

Product width: 220 mm


Product depth: 190 mm

### Electrical Properties

Rated current: 63 A

Main switch (xxA): 63 A

Connection (1/3-phase): 1-phase



### ETIM Product classification: Small distribution board equipped

Mounting method: Cabinet mounted/skeleton unit

Number of rows:

Number of phases: 1

Protection: Miniature-/earth leakage circuit breaker

Number of single-phase miniature circuit breakers (MCB):

Number of three-phase miniature circuit breakers (MCB):

Release characteristic:

Rated short-circuit breaking capacity Icn according to EN 60898 at 230 V:

Power consumption:

Total number of groups: 0

Number of direct groups: 0

Number of light groups: 0

Number of groups behind earth leakage switch: 0

Number of earth leakage circuit breakers: 0

Number of earth leakage switches 30 mA: 0

Number of earth leakage switches 300 mA: 0

Number of arc fault detection devices AFDD: 0

Number of earth leakage circuit breakers/ AFDD:

Protection main switch: No

Number of poles main switch: 2

Main switch rated current: 63 A

Protection incoming RCD: No



Assembly instructions

## Product datasheet:

|                                                                         |         |
|-------------------------------------------------------------------------|---------|
| Protection high integrity:                                              | No      |
| Protection split load:                                                  | No      |
| Protection dual RCD:                                                    | No      |
| Number of outgoing ways:                                                |         |
| Suitable for data:                                                      | No      |
| Cooker group:                                                           | None    |
| Cooker group suitable as power current group:                           | No      |
| With socket outlet:                                                     | No      |
| With bell transformer:                                                  | No      |
| Overvoltage protection:                                                 | No      |
| Type of overvoltage protection device:                                  |         |
| Outgoing connections with connectors for plug-in building installation: |         |
| With meter:                                                             | No      |
| With N-disconnect slide:                                                |         |
| Connection type:                                                        |         |
| Housing material:                                                       | Plastic |
| Degree of protection (IP):                                              | IP20    |
| Height:                                                                 | 190 mm  |
| Built-in height:                                                        |         |
| Width:                                                                  | 220 mm  |
| Built-in width:                                                         |         |
| Width in number of modular spacings:                                    | 12      |
| Depth:                                                                  | 110 mm  |
| Built-in depth:                                                         | 55 mm   |
| Extension possible:                                                     | No      |
| Type of covering:                                                       |         |
| With transparent cover:                                                 | No      |
| Type of closure:                                                        |         |
| Lockable:                                                               | No      |
| Colour:                                                                 |         |
| RAL-number:                                                             |         |

Main switch boxes without output bridge. Easy to install under the Click-mate NXT Distribution boxes or expansion boxes.