

Product datasheet:

XL 115 S Extension boxes

Article number:	➔ AT91413
EAN:	8712259544717

Dimensions / Form

Product width:	115 mm
Product depth:	220 mm

Electrical Properties

Rated current:	32 A
Total number of circuit breakers:	2
Number of individual RCDs (direct):	2
Main switch (xxA):	No
Connection (1/3-phase):	1-phase

ETIM Product classification: Small distribution board equipped

Mounting method:	Surface mounted
Number of rows:	
Number of phases:	1
Protection:	Miniature-/earth leakage circuit breaker
Number of single-phase miniature circuit breakers (MCB):	
Number of three-phase miniature circuit breakers (MCB):	
Release characteristic:	
Rated short-circuit breaking capacity I _{cn} according to EN 60898 at 230 V:	
Power consumption:	
Total number of groups:	2
Number of direct groups:	2
Number of light groups:	0
Number of groups behind earth leakage switch:	0
Number of earth leakage circuit breakers:	0
Number of earth leakage switches 30 mA:	0
Number of earth leakage switches 300 mA:	0
Number of arc fault detection devices AFDD:	
Number of earth leakage circuit breakers/ AFDD:	
Protection main switch:	
Number of poles main switch:	



Assembly instructions

Product datasheet:

Main switch rated current:	
Protection incoming RCD:	
Protection high integrity:	
Protection split load:	
Protection dual RCD:	
Number of outgoing ways:	4
Suitable for data:	
Cooker group:	
Cooker group suitable as power current group:	
With socket outlet:	No
With bell transformer:	No
Overvoltage protection:	
Type of overvoltage protection device:	
Outgoing connections with connectors for plug-in building installation:	
With meter:	No
With N-disconnect slide:	
Connection type:	
Housing material:	Plastic
Degree of protection (IP):	IP20
Height:	220 mm
Built-in height:	
Width:	115 mm
Built-in width:	
Width in number of modular spacings:	6
Depth:	95 mm
Built-in depth:	
Extension possible:	No
Type of covering:	
With transparent cover:	No
Type of closure:	
Lockable:	No
Colour:	
RAL-number:	

Compact Click-mate XL 115 S cabinets. Also suitable as an extension to existing Click-mate XL-plus installations.