

## Product datasheet:

### Consolidation Box

- Suitable for attachment to wiring-duct mounting plate (art. no. AT2228).
- Each cable box includes 2 soft slide-in data lead-ins and 1 slide-in blind cover'.
- Matching AK2 front part can be ordered separately.



**Article number:** **AT1963.01**

**EAN:** 8712259604008

**Packaging quantity:** 15

#### Connections / Entries

**Number of entries:** 10

#### Material / Colour

**Colour:** black

### ETIM Product classification:

#### Box/housing for surface mounting on the wall/ceiling

**Model:**

**Equipped with:** Other

**Max. conductor cross section:**

**Number of poles:**

**Number of clamp positions per pole:**

**Shape:** Rectangular

**Mounting method:** Universal

**Mounting in the soil:** No

**Mounting under water:** No

**Suitable for tube diameter:**

**Number of inlets:** 10

**Inlet from the rear:** No

**Length:** 120 mm

**Width:** 95 mm

**Depth:** 40 mm

**Diameter:**

**Number of cable glands included:**

**Connectable:** No

**Type of housing feed-through:** Preembossing

**With strain relief:**

**Material:** Plastic

**Halogen free:** No

**Surface protection:** Untreated

**Colour:** Black

## Product datasheet:

RAL-number (similar):

|                            |      |
|----------------------------|------|
| Degree of protection (IP): | IP20 |
|----------------------------|------|

|                              |  |
|------------------------------|--|
| Degree of protection (NEMA): |  |
|------------------------------|--|

|              |      |
|--------------|------|
| Cover model: | None |
|--------------|------|

|                                                                         |  |
|-------------------------------------------------------------------------|--|
| Outgoing connections with connectors for plug-in building installation: |  |
|-------------------------------------------------------------------------|--|

|                    |    |
|--------------------|----|
| Transparent cover: | No |
|--------------------|----|

|           |    |
|-----------|----|
| Castable: | No |
|-----------|----|

|                   |            |
|-------------------|------------|
| Cover attachment: | Snapped on |
|-------------------|------------|

|                            |    |
|----------------------------|----|
| Casting compound included: | No |
|----------------------------|----|

|           |    |
|-----------|----|
| Sealable: | No |
|-----------|----|

|                              |       |
|------------------------------|-------|
| Rated insulation voltage Ui: | 690 V |
|------------------------------|-------|

|                    |      |
|--------------------|------|
| Circuit integrity: | None |
|--------------------|------|

|                 |    |
|-----------------|----|
| With screening: | No |
|-----------------|----|

|               |    |
|---------------|----|
| Weatherproof: | No |
|---------------|----|

|                      |             |
|----------------------|-------------|
| Working temperature: | -40 - 70 °C |
|----------------------|-------------|

|                           |    |
|---------------------------|----|
| Explosion-tested version: | No |
|---------------------------|----|

|                           |      |
|---------------------------|------|
| Suitable for Ex-zone gas: | None |
|---------------------------|------|

|                            |      |
|----------------------------|------|
| Suitable for Ex-zone dust: | None |
|----------------------------|------|

The Consolidation Box from Attema makes it possible to install ICT cabling in a flexible manner, because the installation is divided into two steps. The largest portion of the work takes place during the rough construction, at the same time as the other cabling is installed in the building. As a result, you only have to install a small portion of the ICT cabling during the finishing phase. The Consolidation Box complies with the installation standards of EIA/TIA 568A/B, ISO 11801 and NEN-EN 50173.