

Product datasheet:

Electroflex black Ø 32 mm

Flexible conduit

· Internal diameter: Ø 24 mm



Article number: **AT2840**

EAN: 8712259003313

Dimensions / Form

Product inner Ø: 24 mm

ETIM Product classification: Plastic installation tube

Material: Polyvinyl chloride (PVC)

Halogen free: No

Fire retardant version: No

Bending strength: Pliable

Lowest bending radius:

With sleeve: No

Compressive strength class according to EN 61386-1:

Impact strength class according to EN 61386-1:

Flush-mounted installation: No

Surface mounting:

Suitable for installation on wood:

Suitable for hollow wall installation:

Suitable for concrete installation:

Machine and systems installation:

Suitable for underfloor installation (screed):

Suitable for outdoor installation:

Suitable for underground installation:

Inner diameter:

Outer diameter: 32 mm

Operating temperature: -50 - 60 °C

High conducting inner coating: No

With metre indication: No

Colour: Black

RAL-number:

Product datasheet:

Attema has a wide range of flexible conduits for various applications.

Such as ZeroH-flex: halogen-free electroflex, where high(er) demands are made on fire-safe installations. Flame-retardant. KEMA approved according to NEN-EN-IEC 61386-1 and -22. Electroflex for standard electrical applications.

Attaflex, a halogen-free PE-conduit, resistant to higher temperatures and therefore especially suitable for use in concrete. Mantaflex: conduits suitable as thermal insulation material, for central heating or water pipes for instance. Can also be used as a protective hose for electrical connections of machines. And halogen-free Nylonflex, especially suitable for cables in situations where no toxic and corrosive gases may be released in the event of a fire.