

## Product datasheet:

# ZeroH-flex, halogen-free, grey Ø 19 mm

### Flexible conduit

- Sealed package.
- With smooth inner layer (green).



|                 |               |
|-----------------|---------------|
| Article number: | ⇒ AT9518      |
| EAN:            | 8712259303666 |

### Dimensions / Form

|                  |         |
|------------------|---------|
| Product inner Ø: | 14.5 mm |
|------------------|---------|

### ETIM Product classification: Plastic installation tube

|                                                     |                          |
|-----------------------------------------------------|--------------------------|
| Material:                                           | Other                    |
| Halogen free:                                       | No                       |
| Fire retardant version:                             | No                       |
| Bending strength:                                   | Pliable, self recovering |
| Lowest bending radius:                              |                          |
| With sleeve:                                        | No                       |
| Compressive strength class according to EN 61386-1: |                          |
| Impact strength class according to EN 61386-1:      |                          |
| Flush-mounted installation:                         | No                       |
| Surface mounting:                                   |                          |
| Suitable for installation on wood:                  |                          |
| Suitable for hollow wall installation:              |                          |
| Suitable for concrete installation:                 |                          |
| Machine and systems installation:                   |                          |
| Suitable for underfloor installation (screed):      |                          |
| Suitable for outdoor installation:                  |                          |
| Suitable for underground installation:              |                          |
| Inner diameter:                                     | 14,5 mm                  |
| Outer diameter:                                     | 19 mm                    |
| Operating temperature:                              |                          |
| High conducting inner coating:                      | No                       |
| With metre indication:                              | No                       |
| Colour:                                             | Grey                     |
| RAL-number:                                         |                          |

## Product datasheet:

Attema has a wide range of flexible conduits for various applications.

Such as ZeroH-flex: halogen-free electroflex, where high(er) demands are made on fire-safe installations. Flame-retardant. KEMA approved according to NEN-EN-IEC 61386-1 and -22. Electroflex for standard electrical applications.

Attaflex, a halogen-free PE-conduit, resistant to higher temperatures and therefore especially suitable for use in concrete. Mantaflex: conduits suitable as thermal insulation material, for central heating or water pipes for instance. Can also be used as a protective hose for electrical connections of machines. And halogen-free Nylonflex, especially suitable for cables in situations where no toxic and corrosive gases may be released in the event of a fire.