

Product datasheet:

Electroflex cream Ø 16 mm, 100 m

Flexible conduit

- Sealed package.
- Internal diameter: Ø 11.5 mm



Article number: **⇒ AT9510**

EAN: 8712259013176

Dimensions / Form

Product inner Ø: 11.5 mm

ETIM Product classification: Plastic installation tube

Material:	Polyvinyl chloride (PVC)
Halogen free:	No
Fire retardant version:	No
Bending strength:	Pliable
Lowest bending radius:	
With sleeve:	No
Compressive strength class according to EN 61386-1:	
Impact strength class according to EN 61386-1:	
Flush-mounted installation:	No
Surface mounting:	
Suitable for installation on wood:	
Suitable for hollow wall installation:	
Suitable for concrete installation:	
Machine and systems installation:	
Suitable for underfloor installation (screed):	
Suitable for outdoor installation:	
Suitable for underground installation:	
Inner diameter:	11,5 mm
Outer diameter:	16 mm
Operating temperature:	-50 - 60 °C
High conducting inner coating:	
With metre indication:	No
Colour:	Beige
RAL-number:	

Product datasheet:

Attema has a wide range of flexible conduits for various applications.

Such as ZeroH-flex: halogen-free electroflex, where high(er) demands are made on fire-safe installations. Flame-retardant. KEMA approved according to NEN-EN-IEC 61386-1 and -22. Electroflex for standard electrical applications.

Attaflex, a halogen-free PE-conduit, resistant to higher temperatures and therefore especially suitable for use in concrete. Mantaflex: conduits suitable as thermal insulation material, for central heating or water pipes for instance. Can also be used as a protective hose for electrical connections of machines. And halogen-free Nylonflex, especially suitable for cables in situations where no toxic and corrosive gases may be released in the event of a fire.