

## Product datasheet:

# Electroflex cream Ø 16 mm, 10 m

## Flexible conduit

· Internal diameter: Ø 11.5 mm



**Article number:** **↗ AT9516**

**EAN:** 8712259013237

**Packaging quantity:** 10

### Dimensions / Form

**Product inner Ø:** 11.5 mm

### ETIM Product classification: Plastic installation tube

**Material:** Polyvinyl chloride (PVC)

**Halogen free:** No

**Fire retardant version:** No

**Bending strength:** Pliable

**Lowest bending radius:**

**With sleeve:** No

**Compressive strength class according to EN 61386-1:**

**Impact strength class according to EN 61386-1:**

**Flush-mounted installation:** No

**Surface mounting:**

**Suitable for installation on wood:**

**Suitable for hollow wall installation:**

**Suitable for concrete installation:**

**Machine and systems installation:**

**Suitable for underfloor installation (screed):**

**Suitable for outdoor installation:**

**Suitable for underground installation:**

**Inner diameter:** 11,5 mm

**Outer diameter:** 16 mm

**Operating temperature:** -50 - 60 °C

**High conducting inner coating:**

**With metre indication:** No

**Colour:** Beige

**RAL-number:**

## Product datasheet:

Attema has a wide range of flexible conduits for various applications.

Such as ZeroH-flex: halogen-free electroflex, where high(er) demands are made on fire-safe installations. Flame-retardant. KEMA approved according to NEN-EN-IEC 61386-1 and -22. Electroflex for standard electrical applications.

Attaflex, a halogen-free PE-conduit, resistant to higher temperatures and therefore especially suitable for use in concrete. Mantaflex: conduits suitable as thermal insulation material, for central heating or water pipes for instance. Can also be used as a protective hose for electrical connections of machines. And halogen-free Nylonflex, especially suitable for cables in situations where no toxic and corrosive gases may be released in the event of a fire.