

Product datasheet:

UHW50P-CLT CLT-junction box, Perilex

Flush-mounted boxes for solid wooden walls

- Suitable for solid wooden walls.
- Also applicable in hollow walls with a minimum plate thickness of 30 mm.
- Rock-solid mounting in wooden walls, thanks to unique wedge construction.



Article number: **⇒ AT1498**

EAN: 8712259576206

Packaging quantity: 25

Dimensions / Form

Installation opening (wall/ceiling) Ø: 76 mm

Connections / Entries

Number of entries: 2

Assembly / Installation

Assembly type: UP (solid construction)

Safety / Properties

Halogen-free: Yes

Special application: Without



ETIM Product classification:

Box/housing for built-in mounting in the wall/ceiling

Mounting method: Other

Shape: Round

Construction type: Device connection box (round/square)

Model: Single

Provided with revolving ring: No

Couplable: No

Equipped with: None

Diameter: 76,5 mm

Length:

Width:

Depth:

Inner depth: 50 mm

Suitable for wall/board thickness:

Suitable for number of device inserts: 1

Mounting switching equipment: Screwing

With screws: No

Product datasheet:

Number of non-adjustable device fixing lugs:

Number of adjustable device fixing lugs:

Housing feed-through by break-out opening: No

Housing feed-through by seal membrane: No

Housing feed-through by nozzle: No

Housing feed-through by step membrane: No

Suitable for tube diameter:

Suitable for cable diameter: 6 - 10 mm

Pipe locking:

Pipe locking optional: No

Inlet from the rear: No

Number of inlets: 2

Number of included spouts: 0

Material: Plastic

Halogen free: No

Surface protection: Untreated

Colour: Green

Degree of protection (IP): IP20

Degree of protection (NEMA):

Cover model: None

Transparent cover: No

Cover attachment:

Sealable: No

Circuit integrity: None

With screening: No

Airtight: No

Max. conductor cross section: 6 mm²

Number of poles of the clamp:

Clamp position fixed: No

Luminaire hook mounting: No

Nozzle: None

Special application: None

With partition panel:

Compliant with BS 4662:

Securing flush-mounted box in wood? You can mount the CLT flush-mounted boxes from Attema firmly in solid and semi-solid walls. With the CLT flush-mounted boxes from Attema, there is now a suitable solution for mounting switchgear in solid walls. The clamping feet of the standard UHW50 boxes have been replaced by an innovative wedge construction.

Product datasheet:

- Install a flush-mounted box in a wooden wall.
- Rock-solid mounting in wooden walls, thanks to unique wedge construction.
- Directly screwed in a pre-milled hole of Ø 76 mm.
- Attachment with PZ1 screw.
- Also suitable for mounting in semi-solid walls with a panel thickness of 30 mm or more, such as OSB or gypsum fiber panels.
- In addition to the Standard edition, also available in: Fire-resistant, Fire-resistant and smoke-tight, Perilex.