

Product datasheet:

P25 Trunking base + cover, 4 m cream (RAL 1013)

P25/K25 Trunking system (Flat-tube system)

- Quick installation due to attachment holes in 'double' bottom.
- Alignment correction possible thanks to slot and hole pattern in bottom.
- Internal dimensions: 23 x 8 mm




Article number: **AT9272**

EAN: 8712259012773

ETIM Product classification: Mini/maxi trunking

Height:	13 mm
Width:	25 mm
Length:	4.000 mm
Usable cross section:	154 mm ²
Material:	Plastic
Material quality:	Polyvinyl chloride (PVC)
Halogen free:	No
Anti-bacterial treatment:	No
Surface protection:	Untreated
Suitable for circuit integrity:	
Colour:	White
Transparent:	No
RAL-number:	1.013
Number of permanent partitions:	0
Number of plug-in partitions:	0
Type of fastening:	Bottom perforation
Cover model:	Loose
With cable fixing clip:	No
With protective foil:	No
With duct connector:	No
Delivery on roll:	No
Pre-stamping:	No
Degree of protection (IP):	
Impact strength:	
Working temperature:	



Assembly instructions

P25 and K25 are the surface-mounted systems for user-friendly and safe cabling. The cable duct system has a slim and modern design and is suitable for laying complete surface-mounted installations. The unique double bottom construction of the P25 duct

Product datasheet:

allows screw heads to sink safely into the bottom, providing optimum protection for up to 5 VD wires of 2.5 mm². The system is easy to expand with other matching products from the surface-mounted series. All products have the same compact dimensions and are KEMA-approved.