

## Product datasheet:

# P25 Trunking base + cover, 4 m white (RAL 9010)

## P25/K25 Trunking system (Flat-tube system)

- Quick installation due to attachment holes in 'double' bottom.
- Alignment correction possible thanks to slot and hole pattern in bottom.
- Internal dimensions: 23 x 8 mm




**Article number:** **AT9274**

**EAN:** 8712259012797

## ETIM Product classification: Mini/maxi trunking

|                                 |                          |
|---------------------------------|--------------------------|
| Height:                         | 13 mm                    |
| Width:                          | 25 mm                    |
| Length:                         | 4.000 mm                 |
| Usable cross section:           | 154 mm <sup>2</sup>      |
| Material:                       | Plastic                  |
| Material quality:               | Polyvinyl chloride (PVC) |
| Halogen free:                   | No                       |
| Anti-bacterial treatment:       | No                       |
| Surface protection:             | Untreated                |
| Suitable for circuit integrity: |                          |
| Colour:                         | White                    |
| Transparent:                    | No                       |
| RAL-number:                     | 9.010                    |
| Number of permanent partitions: | 0                        |
| Number of plug-in partitions:   | 0                        |
| Type of fastening:              | Bottom perforation       |
| Cover model:                    | Loose                    |
| With cable fixing clip:         | No                       |
| With protective foil:           | No                       |
| With duct connector:            | No                       |
| Delivery on roll:               | No                       |
| Pre-stamping:                   | No                       |
| Degree of protection (IP):      |                          |
| Impact strength:                |                          |
| Working temperature:            |                          |



Assembly instructions

P25 and K25 are the surface-mounted systems for user-friendly and safe cabling. The cable duct system has a slim and modern design and is suitable for laying complete surface-mounted installations. The unique double bottom construction of the P25 duct

## Product datasheet:

allows screw heads to sink safely into the bottom, providing optimum protection for up to 5 VD wires of 2.5 mm<sup>2</sup>. The system is easy to expand with other matching products from the surface-mounted series. All products have the same compact dimensions and are KEMA-approved.