

## Product datasheet:

# WS25 Two-way switch cream (RAL 1013)

## K25/P25 Trunking Accessories

- 10A / 250V with plug-in contacts for solid conductors.
- Consists of base plate with pre-assembled element, cover, rocker operation and mounting hardware.
- Open inlet for flat duct, no separate inlet piece required. Flat duct inlet on other side can be knocked out.
- Integrated stop on base plate for duct and cover.
- Overlaps duct cover by 5 mm. Purely right-angled sawing and sawing to size of the cover is not necessary.
- Knockout in the base plate for rear inlet of duct Ø 16 mm.



**Article number:** **AT5574**

**EAN:** 8712259306582

**Packaging quantity:** 10

### Dimensions / Form

**Product length:** 64 mm

**Product width:** 64 mm

**Product depth:** 46 mm

### ETIM Product classification: Installation switch

**Wiring system:** Two-way switch

**Operating method:** Rocker/button

**Assembly arrangement:** Basic element with housing top

**Number of modules (module system):** 1

**Push button switch:** No

**Number of rockers:** 1

**Mounting method:** Surface mounted

**Type of fastening:** Screw mounting

**With mounting plate:**

**Material:** Plastic

**Material quality:** Thermoplastic

**Halogen free:** No

**Anti-bacterial treatment:** No

**Surface protection:** Untreated

**Surface finishing:** Glossy

**Colour:** White

**RAL-number (similar):** 1.013

**Colour of switch operator:**

## Product datasheet:

|                                                |       |
|------------------------------------------------|-------|
| Label space/information surface:               |       |
| Imprint/indication:                            |       |
| Lighting:                                      |       |
| Function lighting:                             |       |
| Type of lighting:                              |       |
| Suitable for degree of protection (IP):        | IP40  |
| Impact strength:                               |       |
| Nominal voltage:                               | 250 V |
| Rated current:                                 |       |
| Switching current for fluorescent lamps:       | 10 AX |
| Monitoring contact:                            | No    |
| Connection type:                               |       |
| Heating switch:                                | No    |
| Washing machine switch:                        | No    |
| Device width:                                  |       |
| Device height:                                 |       |
| Device depth:                                  |       |
| Device diameter:                               |       |
| Built-in depth:                                |       |
| Min. depth of built-in installation box:       |       |
| Compatible with Apple HomeKit:                 | No    |
| Compatible with Google Assistant:              | No    |
| Compatible with Amazon Alexa:                  | No    |
| IFTTT support available:                       | No    |
| Compliant with UK Building Regulations Part M: |       |

Attema has expanded its sleek, modern and patented K25/P25 Trunking system with a series of contemporary switchgear, especially suitable for flat tubes. This switching material (in cream and white) is distinguished by its compact dimensions, sleek design, easy processing and of course the top quality that you have come to expect from Attema.