

Product datasheet:

ZC25 Double socket cream (RAL 1013)

K25/P25 Trunking Accessories

- 2-pin with rim earthing.
- 16A / 250V with plug-in contacts for solid conductors.
- Consists of base plate with pre-assembled element, cover and mounting hardware.
- Open inlet for flat duct, no separate inlet piece required. Flat duct inlet on other side can be knocked out.
- Integrated stop on base plate for duct and cover.
- Overlaps duct cover by 5 mm. Purely right-angled sawing and sawing to size of the cover is not necessary.
- Knockout in the base plate for rear inlet of duct Ø 16 mm.



Article number: **AT5580**

EAN: 8712259306667

Packaging quantity: 10

Dimensions / Form

Product length: 95 mm

Product width: 64 mm

Product depth: 51 mm

ETIM Product classification:

Socket outlet

Model: Socket outlet with protective contact CEE
7/3 (type F)

Concurrently switching neutral conductor:

Protective contact:

Number of active contacts (round):

Number of active contacts (flat):

Number of active contacts (square):

Mounting direction:

Assembly arrangement:

With signal lamp:

Number of ports USB-A:

Number of ports USB-C:

Max. current rating of USB power supply:

Number of socket outlets:

Socket outlets phase-separated:

Number of modules (module system): 1

Number of socket outlets switchable: 2

Number of phases:

Imprint/indication:

Product datasheet:

Connection type:	
With hinged lid:	No
With enhanced contact protection:	No
Label space/information surface:	No
Colour:	White
RAL-number (similar):	1.013
Metallic colour:	No
Transparent:	
Lockable:	No
Eject-mechanism:	No
Insulated mounting:	
With function lighting:	
With orientation lighting:	
Overvoltage protection:	No
Fault current protection:	No
With miniature fuse:	No
Special power supply:	None
Mounting method:	Surface mounted
Type of fastening:	Mounting with screw
Material:	Plastic
Material quality:	Thermoplastic
Halogen free:	No
Surface protection:	Untreated
Surface finishing:	Glossy
Anti-bacterial treatment:	
With loop through function:	
Number of loop throughs:	
With on/off switch:	
Colour of switch operator:	
Rotated central insert:	No
Nominal current:	16 A
Nominal voltage:	250 V
Frequency:	50 - 60 Hz
Rated fault current:	
Suitable for degree of protection (IP):	IP20
Impact strength:	
Device width:	
Device height:	
Device depth:	
Device diameter:	
Min. depth of built-in installation box:	

Product datasheet:

Compatible with Apple HomeKit:	No
Compatible with Amazon Alexa:	No
Compatible with Google Assistant:	No
IFTTT support available:	No
With Wi-Fi signal repeater:	
With built-in bluetooth speaker:	
For heavy conditions according to VDE:	
Flammability class of insulation material according to UL 94:	
Compliant with UK Building Regulations Part M:	

Attema has expanded its sleek, modern and patented K25/P25 Trunking system with a series of contemporary switchgear, especially suitable for flat tubes. This switching material (in cream and white) is distinguished by its compact dimensions, sleek design, easy processing and of course the top quality that you have come to expect from Attema.