Product datasheet:

Thumbnail clamping plug




K40 Skirting Trunking System

· Quick, screwless mounting of trunking base on a wall.
· Diameter of hole to be drilled in solid gypsum wall: 5 mm

Article number:	**AT9118**
EAN:	8712259012148
Packaging quantity:	100

ETIM Product classification: Hammer-in plug

Drill hole diameter:	5 mm
Mounting thickness:	5 mm
Min. drill hole depth:	
Length:	35 mm
With edge:	No
Material plug:	Plastic
Screwing system:	None
With screw nail:	No
Pin shape:	Nail
Connecting thread metric:	0
Suitable for calcium silicate brick:	No
Suitable for aerated concrete:	No
Suitable for concrete:	No
Suitable for gas concrete:	No
Suitable for solid brick:	No
Push-through installation:	No
Pre-positioned installation:	No
Spaced installation:	No
Colour:	Other



Assembly instructions

The K40 Skirting Trunking System has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 Trunking system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

· The K40 system complies with EN 50085-1 and EN 50085-2-1.
· K40 is suitable for installations 16A/250V~.
· Protection class: IP40 (EN 60529).
· Impact resistance: IK07 (EN 50102).
· Minimum temperature for storage and transport: 5 °C.

Product datasheet:

· Minimum temperature during installation and use: 5 °C.
· Maximum operating temperature: + 60 °C.
· Compartment 1: cross section 350 mm²; maximum number of cables: 2x Ø 10 mm or 1x Ø 13 mm.
· Compartment 2: cross section 640 mm²; maximum number of cables: 3x Ø 10 mm or 2x Ø 13 mm.