

Product datasheet:

ZC40 duplex outlet white (RAL 9010)

K40 Skirting Trunking System

- Duplex with earth connection and child protection.
- 16A / 250V with plug-in contacts for solid conductors.
- Consists of mounting plate with pre-mounted and pre-wired elements, cap and attachment hardware.
- Can be used horizontally or vertically.
- Rotated receptacles so right-angled mains plugs run nicely along the skirting board.
- If necessary, the receptacles can be wired separately.
- Overlap with skirting duct is 5 mm. It is unnecessary to cut the skirting duct cover perfectly square at exactly the right length.



Article number: **➔ AT9214**

EAN: 8712259254395

Packaging quantity: 20

ETIM Product classification: Appliance box for skirting duct

Height baseboard duct: 70 mm

Depth plinth skirting duct: 24 mm

Number of device units:

Equipped with: Socket outlet with safety contact

Mounting method installation unit: Standard

Mounting direction:

Material: Plastic

Halogen free: No

Anti-bacterial treatment: No

Colour: White

RAL-number: 9.010

Decoration: None

Degree of protection (IP):

Impact strength:

Working temperature:



Assembly instructions

The K40 Skirting Trunking System has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 Trunking system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

- The K40 system complies with EN 50085-1 and EN 50085-2-1.
- K40 is suitable for installations 16A/250V~.
- Protection class: IP40 (EN 60529).
- Impact resistance: IK07 (EN 50102).
- Minimum temperature for storage and transport: 5 °C.

Product datasheet:

- Minimum temperature during installation and use: 5 °C.
- Maximum operating temperature: + 60 °C.
- Compartment 1: cross section 350 mm²; maximum number of cables: 2x Ø 10 mm or 1x Ø 13 mm.
- Compartment 2: cross section 640 mm²; maximum number of cables: 3x Ø 10 mm or 2x Ø 13 mm.