Product datasheet:

K40 Skirting duct cover white (RAL 9010)

K40 Skirting Trunking System




· For use as skirting duct.
· Attachment to trunking base via click connection.

Article number:	**AT9237**
EAN:	8712259063140

ETIM Product classification:
Cover for plinth skirting duct

Height:	70 mm
Depth:	24 mm
Length:	2.000 mm
With carpet border:	No
Sealing lip cover:	None
With protective foil:	No
Material:	Plastic
Material quality:	
Halogen free:	No
Colour:	White
RAL-number:	9.010
Decoration:	None
Degree of protection (IP):	
Impact strength:	



Assembly instructions

The K40 Skirting Trunking System has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 Trunking system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

· The K40 system complies with EN 50085-1 and EN 50085-2-1.
· K40 is suitable for installations 16A/250V~.
· Protection class: IP40 (EN 60529).
· Impact resistance: IK07 (EN 50102).
· Minimum temperature for storage and transport: 5 °C.
· Minimum temperature during installation and use: 5 °C.
· Maximum operating temperature: + 60 °C.
· Compartment 1: cross section 350 mm²; maximum number of cables: 2x Ø 10 mm or 1x Ø 13 mm.
· Compartment 2: cross section 640 mm²; maximum number of cables: 3x Ø 10 mm or 2x Ø 13 mm.