Product datasheet:

AZ40 Cover for raceway entry into skirting duct cream (RAL 1013)




K40 Skirting Trunking System

· For vertical branching from the uppermost compartment of the trunking base with raceway P25, K25, Z25 or KK 25x22.

Article number:	**AT9169**
EAN:	8712259012391
Packaging quantity:	50

ETIM Product classification:
Cover for tube-/duct inlet skirting duct

Height baseboard duct:	70 mm
Depth plinth skirting duct:	24 mm
Material:	Plastic
Material quality:	
Halogen free:	No
Colour:	White
RAL-number:	1.013
Degree of protection (IP):	
Impact strength:	



The K40 Skirting Trunking System has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 Trunking system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

· The K40 system complies with EN 50085-1 and EN 50085-2-1.
· K40 is suitable for installations 16A/250V~.
· Protection class: IP40 (EN 60529).
· Impact resistance: IK07 (EN 50102).
· Minimum temperature for storage and transport: 5 °C.
· Minimum temperature during installation and use: 5 °C.
· Maximum operating temperature: + 60 °C.
· Compartment 1: cross section 350 mm²; maximum number of cables: 2x Ø 10 mm or 1x Ø 13 mm.
· Compartment 2: cross section 640 mm²; maximum number of cables: 3x Ø 10 mm or 2x Ø 13 mm.

Assembly instructions