Product datasheet:

E40 End piece crème (RAL1013)




K40 Skirting Trunking System

· Suitable for left or right-side use.
· Can be used in combination with skirting duct cover or symmetric cover strip.
· Overlap with cover strip is 5 mm. It is unnecessary to cut the cover strip perfectly square at exactly the right length.
· Knock-outs for straight or right-angle entry of conduit P25 or KK25x22.

Article number:	**AT9283**
EAN:	8712259254616
Packaging quantity:	20

ETIM Product classification:
End piece for skirting duct



Height:	
Depth:	
Model:	Left/right
Sealing lip cover:	None
Material:	Plastic
Halogen free:	No
Material quality:	
Colour:	White
RAL-number:	1.013
Decoration:	None
With carpet border:	No
Pre-stamping:	No
Degree of protection (IP):	
Impact strength:	

Assembly instructions

The K40 Skirting Trunking System has a modern design and includes extremely compact switching devices that lend themselves to the installation of complete surface-mount systems for 230V, low-voltage and data cabling. K40 is easy to mount and install. Thanks to the symmetric cover strip, vertical applications are also possible. It is simple to expand and offers the flexibility of combination with the K25/P25 Trunking system. It can also be seamlessly integrated with existing systems. The system is extremely well suited for renovation and changing user requirements. The switching devices can easily be moved. The usable storage area for the wiring remains optimal.

· The K40 system complies with EN 50085-1 and EN 50085-2-1.
· K40 is suitable for installations 16A/250V~.
· Protection class: IP40 (EN 60529).
· Impact resistance: IK07 (EN 50102).
· Minimum temperature for storage and transport: 5 °C.
· Minimum temperature during installation and use: 5 °C.
· Maximum operating temperature: + 60 °C.
· Compartment 1: cross section 350 mm²; maximum number of cables: 2x Ø 10 mm or 1x Ø 13 mm.
· Compartment 2: cross section 640 mm²; maximum number of cables: 3x Ø 10 mm or

Product datasheet:

2x Ø 13 mm.