

Product datasheet:

F25 Trunking base + cover, 3 m cream (RAL 1013)

Z25/F25 Cable ducts

- Supplied with special cover for applications in which regulations require that the conduit cannot be opened by hand.
- Includes slots and nail holes.
- Internal dimensions: 22.5 x 10.5 mm




Article number: **↗ AT5611**

EAN: 8712259275352

ETIM Product classification: Mini/maxi trunking

Height:	13 mm
Width:	25 mm
Length:	3.000 mm
Usable cross section:	154 mm ²
Material:	Plastic
Material quality:	Polyvinyl chloride (PVC)
Halogen free:	No
Anti-bacterial treatment:	No
Surface protection:	Untreated
Suitable for circuit integrity:	
Colour:	White
Transparent:	No
RAL-number:	1.013
Number of permanent partitions:	0
Number of plug-in partitions:	0
Type of fastening:	Other
Cover model:	Loose
With cable fixing clip:	No
With protective foil:	No
With duct connector:	No
Delivery on roll:	No
Pre-stamping:	No
Degree of protection (IP):	
Impact strength:	
Working temperature:	



Product datasheet:

Z25 and F25 are the most popular surface-mount systems for installation-friendly data cabling. The clever accessories make it possible to use the entire volume of the ducts for data cables up to Ø 10 mm. Every accessory ensures a minimum bending radius of 25 mm. The clickers and guide pieces make installation quick and easy. The special cover makes the F25 ideal for public areas, such as in Fibre to the Home projects in high-rise buildings and stairways. Since the cover is difficult to remove, it cannot be opened by unauthorised persons and, therefore, the chance of interference in telephone, Internet and television signals is reduced.