

## Product datasheet:

# Cable glands Progress® nickel-plated brass with sealing insert without drilled hole

## Short entry thread metric

- One-piece solid sealing insert
- not overall length insulated
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- When frozen to at least -25°C, the solid sealing inserts are easy to drill.



|                        |                   |
|------------------------|-------------------|
| <b>Article number:</b> | <b>1000.11.30</b> |
| EAN:                   | 7611614131597     |
| Packaging quantity:    | 50                |

### Dimensions / Form

|                  |       |
|------------------|-------|
| Thread:          | Pg 11 |
| Spanner size:    | 21 mm |
| Dimension H:     | 21 mm |
| Thread length L: | 6 mm  |

### Connections / Entries

|                      |                        |
|----------------------|------------------------|
| Max. clamping range: | 12 mm                  |
| clamp technology:    | Compression technology |

### Features


|                |        |
|----------------|--------|
| Thread type:   | metric |
| Thread length: | short  |

### Approvals / Certifications

|                                  |                       |
|----------------------------------|-----------------------|
| Protection class:                | IP 69                 |
| Protection class with condition: | IP 68 (10 bar) / IP69 |

### Storage / Installation / Operation

|                                |        |
|--------------------------------|--------|
| Minimum operating temperature: | -40 °C |
| Maximum operating temperature: | 100 °C |



Assembly instructions



Planning data