

## Product datasheet:

# Cable glands Progress® nickel-plated brass with antikink spring

## Short entry thread metric

### Approval type: Progress MS FKN

- One-piece sealing insert
- overall length insulated
- 1 = Metric coarse-pitch thread (with VDE Testreport)
- Available with sealing inserts conformity with EN 45545 / NFPA 130. When placing an inquiry, prefix the article number by the capital F.
- - Short entry thread with short one-piece or two-piece sealing insert.
- - Long entry thread with short or full-length insulating one-piece or two-piece sealing insert.



**Article number:**  **1060.17.52.080**

**EAN:** 7611614195148

**Packaging quantity:** 10

**Price group:** 540


### Dimensions / Form

**Thread:** M16x1.5

**Spanner size:** 18 mm

**Dimension H:** 66 mm

**Thread length L:** 5 mm



### Connections / Entries

**Min. clamping range:** 6 mm

**Max. clamping range:** 8 mm

**clamp technology:** Compression technology

### Features

**Thread type:** metric

**Thread length:** short

### Approvals / Certifications

**Protection class:** IP 69

**Protection class with condition:** IP 68 (10 bar) / IP69

**VDE:** Yes

### Storage / Installation / Operation

**Minimum operating temperature:** -40 °C

**Maximum operating temperature:** 100 °C



Assembly instructions



Certificates



Planning data